






**METHOD AND SYSTEM FOR IMPROVING HANDOFF IN A CELLULAR NETWORK****Publication number:** EP0995296 (A2)**Publication date:** 2000-04-26**Inventor(s):** SATARASINGHE PRASANNA JAYARAJ [US]**Applicant(s):** NORTEL NETWORKS CORP [CA]**Classification:****- international:** *H04W36/18*; H04W36/00; (IPC1-7): H04M1/00**- European:** H04Q7/38H**Application number:** EP19980935231 19980622**Priority number(s):** WO1998IB01200 19980622; US19970890227 19970709**Also published as:** US6112089 (A) WO9903245 (A2) WO9903245 (A3) CA2295922 (A1) CA2295922 (C)

more &gt;&gt;

Abstract not available for EP 0995296 (A2)

Abstract of corresponding document: **US 6112089 (A)**

A method and system for increasing capacity and improving performance of a cellular network. The method includes maintaining and analyzing matrices of a cell in the network. Once matrix stores performance values and statistics concerning the cell and optimizing conditions for handoff from the cell in response to the performance values. Another matrix stores status values and statistics concerning the cell and optimizing conditions for handoff in response to the status values. A third matrix stores information about cells that should be considered as potential handoff cells.

.....  
Data supplied from the **esp@cenet** database — Worldwide



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b>  <b>H04M</b>	<b>A2</b>	<b>(11) International Publication Number:</b> <b>WO 99/03245</b>  <b>(43) International Publication Date:</b> 21 January 1999 (21.01.99)
<b>(21) International Application Number:</b> PCT/IB98/01200  <b>(22) International Filing Date:</b> 22 June 1998 (22.06.98)  <b>(30) Priority Data:</b> 08/890,227                      9 July 1997 (09.07.97)                      US  <b>(71) Applicant:</b> NORTHERN TELECOM LIMITED [CA/CA]; World Trade Center of Montreal, 8th floor, 380 St. Antoine Street West, Montreal, Quebec H2Y 3Y4 (CA).  <b>(72) Inventor:</b> SATARASINGHE, Prasanna, Jayaraj; 7512 Brown- ley Place, Plano, TX 75025 (US).  <b>(74) Agent:</b> O'NEILL, T., Gary; Gowling, Strathy & Henderson, Suite 2600, 160 Elgin Street, Ottawa, Ontario K1P 1C3 (CA).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>Without international search report and to be republished          upon receipt of that report.</i>
<b>(54) Title:</b> METHOD AND SYSTEM FOR INCREASING CAPACITY AND IMPROVING PERFORMANCE OF A CELLULAR NETWORK  <b>(57) Abstract</b>  A method and system for increasing capacity and improving performance of a cellular network. The method includes maintaining and analyzing matrices of a cell in the network. One matrix stores performance values and statistics concerning the cell and optimizing conditions for handoff from the cell in response to the performance values. Another matrix stores status values and statistics concerning the cell and optimizing conditions for handoff in response to the status values. A third matrix stores information about cells that should be considered as potential handoff cells.		

***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## **METHOD AND SYSTEM FOR INCREASING CAPACITY AND IMPROVING PERFORMANCE OF A CELLULAR NETWORK**

### **Technical Field**

The invention relates generally to cellular telephone systems and, more particularly, to a method and system for increasing capacity for calls and reducing failures during call handoff and call setup in a cellular telephone network.

### **Background of the Invention**

A cellular telephone system serves a defined area by dividing the area into cells. Each cell is served by a single base station, or cell site, and each cell site is connected to a base station controller ("BSC"), which is connected to a message switching center ("MSC"), which is connected to the public switched telephone network ("PSTN"). A mobile unit is connected, or a call is completed, to the PSTN by establishing a radio frequency ("RF") link with a nearby cell site.

The situation in which a mobile unit ends communication with a first cell site and begins communication with a second cell site is referred to as a handoff. A hard handoff occurs when a first RF link between the mobile unit and the first cell site is ended, or dropped, before a second RF link between the mobile unit and the second cell site is established. Alternatively, a soft handoff occurs when the second RF link to the mobile unit is established before the first RF link is dropped. In soft handoff the first cell site is considered the dominant cell while the second cell site is considered a secondary cell. A mobile unit may concurrently enter soft handoff with several different secondary cells.

Soft handoffs typically occur when both cell sites operate on a common radio frequency, such as in a code division multiple access ("CDMA") cellular network. Typically, each cell site operating on the common radio frequency emits a pilot signal. When a mobile unit detects that the strength of a cell site's pilot signal exceeds a certain minimum threshold, it reports a pilot strength measurement ("PSM") message to the BSC via the dominant cell site. Each cell has its own list of potential handoff candidates, or neighbor list, and if the cell site, or pilot, associated with the pilot signal is in the neighbor list

for the dominant cell, then the BSC informs the mobile unit to add the pilot to the mobile unit's Active Set. An Active Set is a list of secondary cells currently in soft handoff, or Active Set Pilots, maintained by the mobile unit. As a result, the BSC can thereby select the appropriate secondary cells for the mobile unit to enter soft handoff.

A detailed description of soft handoff parameters, terms, and procedures is disclosed in "*Mobile Station-Base Compatibility Standard for Dual-Mode Wide Band Spread Spectrum Cellular System*" TIA/EIA/IS-95-A Standard, March 15, 1995, which is hereby incorporated by reference.

Under this procedure, however, the mobile unit may enter into soft handoff with undesired secondary cells. For example, although the pilot signal from the secondary cell exceeds the minimum threshold, the secondary cell site may be in a location that will improperly service the mobile unit due to other factors or obstructions not yet detected by the mobile unit, which could result in a dropped call. In addition, many pilot signals may exceed the minimum threshold such that soft handoff occurs with each associated secondary cell, requiring an extensive load on the BSC which could result in lost call capacity. Also, since each cell site has a finite number of channel elements with which to link to a mobile unit, each channel element unnecessarily used for soft handoff is thereby unavailable for other calls.

### **Summary of the Invention**

The present invention, accordingly, provides a method and system for increasing capacity and improving performance of a cellular network by improving the conditions for handoff. In one embodiment the method optimizes the performance of the cellular telephone network by maintaining a matrix of performance values concerning a cell in the network and adjusting certain conditions for handoff in response to the performance values. Examples of performance values include frequency statistics of successful handoffs to a second cell of the cellular telephone network, frequency statistics of failed handoffs to the second cell because the second cell was removed from the first cell's neighbor list, and frequency statistics of failed handoffs to the second cell because the second cell had insufficient resources.

In another embodiment, the method optimizes the performance of the cellular network by maintaining a matrix of status values concerning the cell and adjusting the conditions for handoff in response to the status values. Examples of the status values include a pilot signal strength measurement for the second cell and a round trip delay measurement from the second cell to the mobile unit. With the status values, a determination can be made to remove the second cell from the mobile unit's Active Set if either the pilot signal strength for the second cell falls below a predetermined threshold or the round trip delay value exceeds a predetermined maximum.

In yet another embodiment, the method optimizes the neighbor list for the cell by maintaining a second list of cells that are not in the neighbor list but have had their pilot signals reported by the mobile unit operating in the dominant cell. Furthermore, the pilot signal strength for the reported cells is tracked, along with the number of occurrences with which any particular cell has been reported. As a result, a determination can be made as to whether to include certain cells in the neighbor list.

A technical advantage achieved is that cost of the cellular network is minimized due to an increased call capacity.

Another technical advantage achieved is that the potential of handing off a call to an undesired cell is greatly reduced.

Another technical advantage achieved is that the cellular network dynamically adapts to its environment.

### **Brief Description of the Drawings**

Fig. 1 illustrates a cellular telephone network embodying features of the present invention.

Fig. 2 is a flow chart for a method for optimizing the cellular network of Fig. 1.

Fig. 3 is a flow chart of a soft handoff management method for use by the optimization method of Fig. 2.

### Description of a Preferred Embodiment

Referring to Fig. 1, the reference numeral 10 designates a cellular telephone network operating on a common frequency. The network 10 has six cells C1, C2, C3, C4, C5, and C6. Each cell C1-C6 is connected to and serviced by a BSC 12, which in turn is connected to and serviced by an MSC (not shown). A mobile unit 14 is operating in the network 10 and for the sake of example is initially located in and linked to the cell C1 (the dominant cell). As the mobile unit 14 moves around cell C1, it receives pilot signals from one or more of the remaining cells of the network 10, and if the strength of a received pilot signal exceeds a threshold value T\_ADD, the mobile unit 14 sends a PSM message to the BSC 12 via the cell C1. For the remaining description, the disclosed functionality will be performed by the BSC 12, it being understood that other components of the network 10, including those not shown, may alternatively provide or assist in the disclosed functionality.

Referring to Fig. 2, whenever the mobile unit 14 initiates a call, the BSC 12 performs an optimization routine 20. At step 21 a PSM message is received from the mobile unit 14. It is understood that if the mobile unit 14 never detects a pilot signal that exceeds the threshold value T\_ADD, the mobile unit will never send a PSM message and the optimization routine 20 will not be completed. At step 22, upon receipt of the PSM message from the mobile unit 14, the BSC 12 determines if the pilot indicated by the PSM message is in the neighbor list ("N\_LIST") 23 for the dominant cell. The N\_LIST 23 contains a pilot number ("PN") offset for all potential Active Set Pilots for mobile units operating in the dominant cell C1. It is also understood that the N\_LIST 23 may be initially determined by the radio frequency ("RF") design of the network 10. For example, the N\_LIST 23 may include the PN offsets for cells C2, C4 and C5. However, as will become evident in the following discussion, the N\_LIST 23 will be optimized due to actual performance characteristics of the network 10.

If the PN offset is in the N\_LIST 23, execution proceeds to step 24 in which a soft handoff management routine is performed to update two matrices: a status matrix and a performance matrix, both described in greater detail

below. If at step 22 the PN offset is not in the N\_LIST 23, execution proceeds to step 26 in which a pilot consideration matrix is updated, which is also described in greater detail below. Upon completion of steps 24 or 26, execution returns to step 21. Furthermore, as the pilot consideration matrix is updated,  
 5 it can be used to optimize the N\_LIST 23. Such optimization may occur more frequently during initial operation of the network 10 and less frequently thereafter.

The pilot consideration matrix is updated for each cell indicated by a PSM message that is not in the N\_LIST. Table 1 below illustrates an  
 10 exemplary pilot consideration matrix for the dominant cell C1. The columns of Table 1 represent certain parameters of these pilot signals, including the PN offset value, the strongest measured PSM for the cell, and the number of times the pilot signal has been reported. The rows represent the individual cells that are under consideration, the number of rows being dynamic. The pilot  
 15 consideration matrix Table 1 provides an indication of important cells missing from the N\_LIST and can be used at a later time to optimize the N\_LIST for a certain cell. This table is important for an operating cellular network to identify network interference and take remedial action to improve the network's performance. Also, this allows the cellular network 10 to be  
 20 responsive to changes in its environment.

**Table 1:**

	PN offset	Pilot Strength	No. of Occurrences
cell C3			
cell C6			
cell Cn			

25 Referring to Fig. 3, the soft handoff management routine 24 begins at step 28 where the performance matrix 30a and the status matrix 30b are updated. The matrices 30a and 30b are updated according to certain predefined performance and status criteria, examples of which are described below.



The performance matrix 30a is maintained for each cell C1-C6 of the network 10. Table 2 below illustrates an exemplary performance matrix for the cell C1. The columns of Table 2 represent the cells in the N\_LIST for the cell C1. In continuance of the example described above, the columns are initially C2, C4, and C5. The rows of Table 2 designate counters for certain performance measurements. For the sake of example, five rows R1, R2, R3, R4, and R5 are defined as follows:

R1: successful handoffs;

R2: handoff failures due to a secondary cell being removed from the mobile unit's Active Set for having a pilot signal below a certain threshold value T\_DROP.

R3: handoff failures due to a lack of available channel elements;

R4: handoff failures due to reasons other than R2 or R3;

R5: handoff failures due to the soft handoff management routine 24 (Fig. 3).

Each (row, column) entry of Table 2 may be incremented for each operation of step 24. For example, if a successful soft handoff is performed with the cell C2, then the counter for (R1, C2) is incremented. If however, an attempted soft handoff to the cell C4 fails because no channel elements of the cell C4 are available, then the counter for (R3, C4) is incremented.

**Table 2:**

	C2	C4	C5
R1	1		
R2			
R3		1	
R4			
R5			

A status matrix 30b is also maintained for each cell C1-C6 of the network 10. Table 3 below illustrates an exemplary status matrix for the dominant cell C1. The columns of Table 3 represent all the cells with which the mobile units operating in cell C1 are in soft handoff during the duration of

the call, i.e., Active Set Pilots ASP1, ASP2 ... ASPn. The Active Set Pilots are derived from the N\_LIST 23 as well as the N\_LISTs of the other cells with which the mobile units are in soft handoff. At any given time, there may be a different number of Active Set Pilots for any one mobile unit and therefore the number of columns in the status matrix is dynamic. However, practical constraints limit the number of Active Set Pilots to six. The rows of Table 3 represent certain status measurements associated with each mobile unit while in communication with each Active Set Pilot. For the sake of example, eight rows R6, R7, R8, R9, R10, R11, R12 and R13 are defined as follows:

R6: strength of the last reported pilot signal from the Active Set Pilot;

R7: strength of the pilot signal of the Active Set Pilot before soft handoff was initiated;

R8: the most recent round trip delay ("RTD") measurement from the cell site of the Active Set Pilot to the mobile unit 14;

R9: extra RF link capacity for the cell site of the Active Set Pilot;

R10: number of channel elements available in the cell site of the Active Set Pilot;

R11: status of the Active Set Pilot, the status being either 1) current "C", 2) most recently removed from the Active Set "MR", 3) removed from the Active Set "R", or 4) not added to the Active Set "NA";

R12: strength of the pilot signal of the Active Set Pilot when it was removed from the Active Set;

R13: a reason for removing the Active Set Pilot from the Active Set, the reason being either 1) handoff failures due to a pilot signal strength falling below a predetermined minimum threshold, 2) handoff failure due to any other reason; 3) the RTD exceeds maximum, 4) there are no available channel elements, 5) there are no available RF links, 6) the pilot signal designates an undesirable cell.

Each (row, column) entry of Table 3 contains information that may be updated for each operation of step 24. For example, an RTD maximum value is specified for each cell, such as ASP2. The RTD maximum value represents a

maximum distance in which a mobile unit can be from the corresponding cell site and maintain a reliable RF link. On occasion, the pilot signal from ASP2 may be strong (e.g., a measurement of "Y" decibels where  $Y > T\_ADD$ ) but the RTD distance will be too great (e.g., a distance of "X" meters, where  $X >$  the RTD maximum value). In these occasions, the particular cell is undesirable for soft handoff because the mobile unit is outside the cell's intended coverage area and the status matrix is updated as described below in Table 3.

**Table 3:**

	ASP1	ASP2	ASP3	ASPn
R6		Y		
R7				
R8		X		
R9				
R10				
R11				
R12		Y		
R13		3		

Referring again to Fig. 3, after the matrices 30a, 30b have been updated in step 32, execution proceeds to step 34 where new pilots may be added to the Active Set Pilots. For a new pilot to be added to the Active Set Pilots, the PSM for the pilot must be within a predefined threshold  $T\_NADD$  of the signal strength of the strongest pilot in the Active Set. In this way, the number of pilot signals that are strong enough to be reported (exceed the  $T\_ADD$  threshold) but are not comparatively strong (do not fall within the  $T\_NADD$  threshold of the strongest pilot signal) are not added to the Active Set Pilots, thereby saving capacity of the network 10.

To further improve capacity, at step 36, any undesirable pilots are removed. For example, if the counters R8, R9, and/or R10 for any of the Active Set Pilots ASP1 ... ASPn have been activated, the counter R6 is examined for every Active Set Pilot and compared with the signal strength of the strongest Active Set Pilot. If the signal strength of any Active Set Pilot is not within a

predefined threshold T\_REMOVE (similar to T\_NADD), the corresponding pilot is removed from the Active Set. When a pilot is removed from the Active Set, the appropriate counters R11, R12, R13 are updated for that pilot. When updating the counter R12, any counter with the value "MR" is replaced with the value "R" and the counters for any recently removed ASP's are given the value "MR".

At step 38, certain ones of the pilots may be re-admitted to the Active Set. For example, the counter R6 and R7 may be examined and if the signal strength of a pilot that has been removed from the Active Set is within a predefined threshold T\_DROPADD (similar to T\_REMOVE and T\_NADD), the corresponding pilot may be readmitted to the Active Set. In addition, since the most recently removed pilots are indicated by the counter R12, the corresponding pilots may also be readmitted, as required.

Although illustrative embodiments of the invention have been shown and described, other modifications, changes, and substitutions are intended in the foregoing disclosure. For examples, a single threshold value can be substituted for several of the above identified thresholds. Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the invention.

## WHAT IS CLAIMED IS:

- 1 1. A method for optimizing the performance of a cellular telephone network  
2 including a first cell and a mobile unit located therein, the method comprising  
3 maintaining performance values concerning the cell; and adjusting conditions  
4 for handoff in response to the performance values, the performance values  
5 including frequency of successful handoffs to a second cell of the cellular  
6 telephone network, frequency of failed handoffs to the second cell because the  
7 second cell was removed from a list of handoff cells, and frequency of failed  
8 handoffs to the second cell because the second cell had insufficient resources.
- 1 2. The method of claim 1 wherein the first and second cell operate on a  
2 common frequency and wherein the handoff is a soft handoff.
- 1 3. The method of claim 1 further comprising maintaining status values  
2 concerning the cell and adjusting conditions for handoff in response to the  
3 status values, the status values including a pilot signal strength measurement  
4 for the second cell, and a round trip delay measurement from the second cell to  
5 the mobile unit, and wherein the second cell is removed from the list of handoff  
6 cells if the pilot signal strength measurement for the second cell falls below a  
7 predetermined threshold or if the round trip delay measurement exceeds a  
8 predetermined maximum.
- 1 4. The method of claim 3 wherein the status values further include:  
2 a designation for available hardware resource of the second cell; and  
3 a reason for removing the second cell from the list of handoff cells.
- 1 5. The method of claim 3 wherein the status values further include a  
2 designation of whether the second cell is current, removed, or most recently  
3 removed.

1 6. A method for optimizing the performance of a cellular telephone network  
2 including a first cell and a mobile unit located therein, the method comprising  
3 maintaining of status values concerning the cell and adjusting conditions for  
4 handoff in response to the status values, the status values including a pilot  
5 signal strength measurement for the second cell; and a round trip delay  
6 measurement from the second cell to the mobile unit; such that the second cell  
7 is removed from a list of handoff cells if the pilot signal strength measurement  
8 for the second cell falls below a predetermined threshold or if the round trip  
9 delay measurement exceeds a predetermined maximum.

1 7. The method of claim 6 wherein the status values further include a  
2 designation for available hardware resource of the second cell, and a reason for  
3 removing the second cell from the list of handoff cells.

1 8. The method of claim 6 wherein the status values further include a  
2 designation of whether the second cell is current, removed, or most recently  
3 removed.

1 9. A method for managing soft handoff of a mobile unit from a dominant  
2 cell to a secondary cell, both of a common-frequency cellular telephone network,  
3 the method comprising:

4 maintaining performance values for the dominant cell, the performance  
5 values including a frequency of successful handoffs to the secondary cell, a  
6 frequency of failed handoffs to the secondary cell because the secondary cell  
7 was removed from a list of handoff cells, and a frequency of failed handoffs to  
8 the secondary cell because the secondary cell had insufficient resources;

9 maintaining status values for the dominant cell, the status values  
10 including a pilot signal strength measurement for the secondary cell, a  
11 designation for available hardware resource of the secondary cell, a reason for  
12 removing the secondary cell from the list of handoff cells, and a designation of  
13 whether the secondary cell is current, removed, or most recently removed from  
14 the list of handoff cells;

15 adding the secondary cell to the list of handoff cells if the pilot signal  
16 strength for the secondary cell exceeds a first predetermined threshold;  
17 removing the secondary cell to the list of handoff cells if the pilot signal  
18 strength for the secondary cell falls below a second predetermined threshold;  
19 and  
20 re-adding the secondary cell to the list of handoff cells if the pilot signal  
21 strength for the secondary cell exceeds a third predetermined threshold and the  
22 designation of the secondary cell is most recently removed.

1 10. A method of optimizing a first list of potential handoff cells for a  
2 dominant cell of a cellular telephone network, the method comprising:  
3 maintaining a second list of cells that are not in the first list but have  
4 had their pilot signals reported by a mobile unit operating in the dominant cell;  
5 tracking a signal strength for the reported pilot signals of the cells in the  
6 second list; and  
7 tracking a number of times that the pilot signals have been reported for  
8 the cells in the second list.

1 11. The method of claim 10 wherein, after a period of time, the tracked  
2 signal strength and tracked number of times for each pilot signal of the second  
3 list is analyzed to determine whether the corresponding cell should be included  
4 in the first list.

1 12. A system for managing soft handoff of a mobile unit from a dominant cell  
2 to a secondary cell, both of a common-frequency cellular telephone network, the  
3 system comprising:  
4 a matrix of performance values for the dominant cell, the performance  
5 values including a frequency of successful handoffs to the secondary cell, a  
6 frequency of failed handoffs to the secondary cell because the secondary cell  
7 was removed from a list of handoff cells, and a frequency of failed handoffs to  
8 the secondary cell because the secondary cell had insufficient resources;

a matrix of status values for the dominant cell, the status values including a pilot signal strength measurement for the secondary cell, a designation for available hardware resource of the secondary cell, a reason for removing the secondary cell from the list of handoff cells, and a designation of whether the secondary cell is current, removed, or most recently removed from the list of handoff cells;

means for adding the secondary cell to the list of handoff cells if the pilot signal strength for the secondary cell exceeds a first predetermined threshold;

means for removing the secondary cell to the list of handoff cells if the pilot signal strength for the secondary cell falls below a second predetermined threshold; and

means for re-adding the secondary cell to the list of handoff cells if the pilot signal strength for the secondary cell exceeds a third predetermined threshold and the designation of the secondary cell is most recently removed.

13. A system for optimizing a first list of potential handoff cells for a dominant cell of a cellular telephone network, the system comprising:

a second list of cells that are not in the first list but have had their pilot signals reported by a mobile unit operating in the dominant cell;

means for tracking a signal strength for the reported pilot signals of the cells in the second list;

means for tracking a number of times that the pilot signals have been reported for the cells in the second list; and

means for analyzing the tracked signal strength and tracked number of times for each cell of the second list to determine whether that cell should be included in the first list.







FIG. 2

FIG. 3




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04Q 7/34, 7/38</b>		<b>A3</b>	(11) International Publication Number: <b>WO 99/03245</b>
			(43) International Publication Date: 21 January 1999 (21.01.99)
(21) International Application Number: PCT/IB98/01200		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 22 June 1998 (22.06.98)			
(30) Priority Data: 08/890,227 9 July 1997 (09.07.97) US			
(71) Applicant: NORTHERN TELECOM LIMITED [CA/CA]; World Trade Center of Montreal, 8th floor, 380 St. Antoine Street West, Montreal, Quebec H2Y 3Y4 (CA).			
(72) Inventor: SATARASINGHE, Prasanna, Jayaraj; 7512 Brown- ley Place, Plano, TX 75025 (US).		<b>Published</b> <i>With international search report.</i>	
(74) Agent: O'NEILL, T., Gary; Gowling, Strathy & Henderson, Suite 2600, 160 Elgin Street, Ottawa, Ontario K1P 1C3 (CA).		(88) Date of publication of the international search report: 1 April 1999 (01.04.99)	

**(54) Title:** METHOD AND SYSTEM FOR INCREASING CAPACITY AND IMPROVING PERFORMANCE OF A CELLULAR NETWORK

**(57) Abstract**

A method and system for increasing capacity and improving performance of a cellular network. The method includes maintaining and analyzing matrices of a cell in the network. One matrix stores performance values and statistics concerning the cell and optimizing conditions for handoff from the cell in response to the performance values. Another matrix stores status values and statistics concerning the cell and optimizing conditions for handoff in response to the status values. A third matrix stores information about cells that should be considered as potential handoff cells.



***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

<b>AL</b>	Albania	<b>ES</b>	Spain	<b>LS</b>	Lesotho	<b>SI</b>	Slovenia
<b>AM</b>	Armenia	<b>FI</b>	Finland	<b>LT</b>	Lithuania	<b>SK</b>	Slovakia
<b>AT</b>	Austria	<b>FR</b>	France	<b>LU</b>	Luxembourg	<b>SN</b>	Senegal
<b>AU</b>	Australia	<b>GA</b>	Gabon	<b>LV</b>	Latvia	<b>SZ</b>	Swaziland
<b>AZ</b>	Azerbaijan	<b>GB</b>	United Kingdom	<b>MC</b>	Monaco	<b>TD</b>	Chad
<b>BA</b>	Bosnia and Herzegovina	<b>GE</b>	Georgia	<b>MD</b>	Republic of Moldova	<b>TG</b>	Togo
<b>BB</b>	Barbados	<b>GH</b>	Ghana	<b>MG</b>	Madagascar	<b>TJ</b>	Tajikistan
<b>BE</b>	Belgium	<b>GN</b>	Guinea	<b>MK</b>	The former Yugoslav	<b>TM</b>	Turkmenistan
<b>BF</b>	Burkina Faso	<b>GR</b>	Greece		Republic of Macedonia	<b>TR</b>	Turkey
<b>BG</b>	Bulgaria	<b>HU</b>	Hungary	<b>ML</b>	Mali	<b>TT</b>	Trinidad and Tobago
<b>BJ</b>	Benin	<b>IE</b>	Ireland	<b>MN</b>	Mongolia	<b>UA</b>	Ukraine
<b>BR</b>	Brazil	<b>IL</b>	Israel	<b>MR</b>	Mauritania	<b>UG</b>	Uganda
<b>BY</b>	Belarus	<b>IS</b>	Iceland	<b>MW</b>	Malawi	<b>US</b>	United States of America
<b>CA</b>	Canada	<b>IT</b>	Italy	<b>MX</b>	Mexico	<b>UZ</b>	Uzbekistan
<b>CF</b>	Central African Republic	<b>JP</b>	Japan	<b>NE</b>	Niger	<b>VN</b>	Viet Nam
<b>CG</b>	Congo	<b>KE</b>	Kenya	<b>NL</b>	Netherlands	<b>YU</b>	Yugoslavia
<b>CH</b>	Switzerland	<b>KG</b>	Kyrgyzstan	<b>NO</b>	Norway	<b>ZW</b>	Zimbabwe
<b>CI</b>	Côte d'Ivoire	<b>KP</b>	Democratic People's	<b>NZ</b>	New Zealand		
<b>CM</b>	Cameroon		Republic of Korea	<b>PL</b>	Poland		
<b>CN</b>	China	<b>KR</b>	Republic of Korea	<b>PT</b>	Portugal		
<b>CU</b>	Cuba	<b>KZ</b>	Kazakstan	<b>RO</b>	Romania		
<b>CZ</b>	Czech Republic	<b>LC</b>	Saint Lucia	<b>RU</b>	Russian Federation		
<b>DE</b>	Germany	<b>LI</b>	Liechtenstein	<b>SD</b>	Sudan		
<b>DK</b>	Denmark	<b>LK</b>	Sri Lanka	<b>SE</b>	Sweden		
<b>EE</b>	Estonia	<b>LR</b>	Liberia	<b>SG</b>	Singapore		

## INTERNATIONAL SEARCH REPORT

Internatic Application No

PCT/IB 98/01200

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04Q7/34 H04Q7/38

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	CHANG SOON KANG ET AL: "CDMA MOBILE COMMUNICATION SYSTEM PERFORMANCE ANALYSIS TOOLS FOR NETWORK PARAMETER PLANNING" 1996 IEEE 46TH. VEHICULAR TECHNOLOGY CONFERENCE, MOBILE TECHNOLOGY FOR THE HUMAN RACE ATLANTA, APR. 28 - MAY 1, 1996, vol. 2, no. CONF. 46, 28 April 1996, pages 894-898, XP000593104 INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS see page 896, column 2, line 10 - line 48 ---	1
A	EP 0 701 382 A (AT & T CORP) 13 March 1996 see abstract see column 8, line 13 - line 39 --- -/--	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## ° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&amp;" document member of the same patent family

Date of the actual completion of the international search

8 January 1999

Date of mailing of the international search report

20/01/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Fernandez Balseiro, J

## INTERNATIONAL SEARCH REPORT

Internati Application No

PCT/IB 98/01200

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 267 261 A (BLAKENEY II ROBERT D ET AL) 30 November 1993 see abstract see column 3, line 25 - column 4, line 43 ---	2,3,6, 9-13
A	US 5 428 816 A (BARNETT CHARLES A ET AL) 27 June 1995 see abstract see column 2, line 14 - line 60 ---	9-13
A	US 5 327 575 A (MENICH BARRY J ET AL) 5 July 1994 see abstract see column 4, line 44 - line 63 -----	3,6,9

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 98/01200

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0701382 A	13-03-1996	US 5623535 A JP 8116568 A	22-04-1997 07-05-1996
US 5267261 A	30-11-1993	US 5640414 A	17-06-1997
US 5428816 A	27-06-1995	NONE	
US 5327575 A	05-07-1994	CA 2109508 A DE 69319821 D EP 0591478 A JP 6508497 T KR 9702762 B SK 131093 A WO 9319560 A	24-09-1993 27-08-1998 13-04-1994 22-09-1994 10-03-1997 10-08-1994 30-09-1993